

EcoLink Downlight



| | | |
|----------------|------------------------------|------------------------|
| optical system | Lumen output | 600/900/1200/1500/2000 |
| | CRI | ≥80 |
| | CCT | WW/CW |
| Electronics | Input Voltage and Frenquency | 220-240V, 50/60Hz |
| | Lifetime | 15,000 H |
| | Power consumption (system) | 6.5/12/16 |
| | Conventional Replacement | |
| | System Efficacy | 75 - 92lm/W |
| Mechanics | Material | Polycarbonat |
| | IPxx | IP20 |
| | Shape | Round |
| | Driver | Integrated |
| | Size | 3.5"/5"/6"/7"/8" |
| Approbation | Approbation | SNI |
| | Warranty | 1 year |
| Accessories | Clip, braket, Connector | Clip |

| Material description | Size | CCT (K) | Watt | Lumen (lm) | Life Time (Hours) |
|----------------------------------|------|---------|-------|------------|-------------------|
| EDN200B LED6 6.5W 220-240 D90 | 3.5" | CW / WW | 6.5 W | 600 | 15000 |
| EDN200B LED9 12W 220-240 D125 | 5" | CW / WW | 12 W | 900 | 15000 |
| EDN200B LED12 16W 220-240 D150 | 6" | CW / WW | 16 W | 1200 | 15000 |
| EDN200B LED15 20W 220-240 D175 | 7" | CW / WW | 20 W | 1500 | 15000 |
| EDN200B LED20 24.5W 220-240 D200 | 8" | CW / WW | 24.5W | 2000 | 15000 |