

EcoLink Bulb



optical system	Lumen output	520, 700, 900, 1250
	CRI	≥80
	CCT	3000K / 6500K
Electronics	Input Voltage and Frequency	100-250V, 50/60Hz
	Lifetime	15,000 H
	Driver	Integrated
	Power consumption (system)	6,8,10,12W
	System Efficacy	up to 104lm/W
Mechanics	Material	Polycarbonat
	IPxx	IP20
	Fitting	E27
Approbation	Approbation	SNI
	Warranty	1 year
Accessories	Clip, braket, Connector	-

Material description	Cap	Replaced Wattage (W)	CCT (K)	Lumen (lm)	Life Time (Hours)
Ecolink LED Bulb 6W E27 3000K 1CT/12	E27	50(50W GLS, 9W CFL)	3000	520	15000
Ecolink LED Bulb 6W E27 6500K 1CT/12	E27	50(50W GLS, 9W CFL)	6500	520	15000
Ecolink LED Bulb 8W E27 3000K 1CT/12	E27	65(65W GLS, 12W CFL)	3000	700	15000
Ecolink LED Bulb 8W E27 6500K 1CT/12	E27	65(65W GLS, 12W CFL)	6500	700	15000
Ecolink LED Bulb 10W E27 3000K 1CT/12	E27	80(80W GLS, 15W CFL)	3000	900	15000
Ecolink LED Bulb 10W E27 6500K 1CT/12	E27	80(80W GLS, 15W CFL)	6500	900	15000
Ecolink LED Bulb 12W E27 3000K 1CT/12	E27	20(95W GLS, 20W CFL)	3000	1250	15000
Ecolink LED Bulb 12W E27 6500K 1CT/12	E27	20(95W GLS, 20W CFL)	6500	1250	15000